

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Lira 140 Led Square

Code : 4142684W

PRODUCT FAMILY

IP67 Inground/ wall LED Uplight or false ceiling mounting Downlight.

MATERIAL CHARACTERISTICS

Body in anodised, die-cast aluminium alloy EN AB 46100
 Ring in S.Steel AISI 316L with 2.5mm thickness and micro-shot blasted
 Diffuser in flat, tempered glass, and with a thickness of 8mm
 Colour: S.Steel
 Gaskets in silicone
 Screws in stainless steel A2

LIGHTING CHARACTERISTICS

Adjustable optics - +/- 15° (GU10 version only)
 1 monochromatic Led module 8.7W SEOUL 4000K neutral white (NW) 800 lm, or 3000K warm white (WW) 800 lm. DIRECT SUPPLY TENSION 220-240V 50/60Hz
 1 monochromatic Led 9.3W CREE 4000K neutral white (NW) 666 lm, or 3000K warm white (WW) 618 lm with beam optics 20°, 40°, 80°x20°, supplied in 700mA
 Fitting designed for Led lamp PAR16 GU10 lamp holder supply tension 220-240V 50-60Hz
 Immediately ON at 100% of light flux

WIRING CHARACTERISTICS

Factory-sealed termination chamber – utilising resin to guarantee sealing
 40cm of H05 RN-F 2x1mmq cable supplied with PG9 cable gland (version with LED CREE circuit), IPSC Protected against Reversal of polarity, Overvoltage and Short circuit electronic driver for 700mA not supplied
 40cm of H05 RN-F 3x1mmq cable supplied with PG9 cable gland (version with 230V led SEOUL circuit), direct mains supply 230V
 40cm of H05 RN-F 3x1mmq cable supplied with PG9 cable gland (version for LED lamp not supplied GU10), direct mains supply 230V

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Ceiling downlight for direct mounting, requiring Ø126mm hole with locking mechanism (supplied separately)
 - Inground/wall light for use with recessed box accessory (supplied separately)
 Ordinary maintenance (usually unnecessary for LED products) by removing the n.4 screws from ring and removing diffuser

MEASUREMENT CHARACTERISTICS

Square ring 140x140mm (with 2.5mm height)
 Depth 122.5mm
 Maximum drive-over load: 2500Kg at 20Km/h

ACCESSORIES

- Compulsory for pavement mounting
 Recessed box (code: 7000.0005)

- Compulsory for false ceiling mounting
 locking mechanism kit (code. 4000000W)

Optional:

Electronic driver 700mA 33W (Cod. CS160020)
 IP68 connector (Cod. CS093000)
 "T"-3 way IP68 connector (Cod. CS093001)

print free coupons click petmart pharmacy coupon code

Details

• Conformity with CEE directives

- Class III
- Mounting on normal flammable surface
- Energy-saving fittings
- Electronic supply
- Resistant to atmospheric agents
- Inalterable to ultraviolet radiations
- Ground recessed
- Wall recessed
- Drive over
- IP 67

