



## STREETLIGHT PHOTOMETRIC TEST REPORT

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 28.47 lm/W
MODEL	DLW-LED-066-20W-3000K	I <sub>max</sub> (cd)	268.3	η street_up (%)	0.8	
NOMINAL POWER (W)	20	LOR (%)	100.0	η street_down (%)	50.6	
RATED VOLTAGE (V)	220	TOTAL FLUX (lm)	595.1	η house_up (%)	0.8	
NOMINAL FLUX (lm)	595.088	MAXIMUM @ (C, γ )	220,40.0	η house_down (%)	47.8	
LAMPS INSIDE	1	η up (%)	1.6	76 FLASHAREA (m2)	0.00100	
TEST VOLTAGE (V)	219.8	η down (%)	98.4	SLI	14.566	


INTENSITY DISTRIBUTION DIAGRAM  
IN C PLANSMAX INTENSITY CONE SURFACE  
DISTRIBUTION DIAGRAM

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks:

## STREETLIGHT ISOCANDELA DIAGRAM

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:





## Classification:

IES:Type V - Very Short  
CIE:Narrow - Short  
IES:Cut-off  
CIE:Semi-cut-off  
Max.At80:83.48cd/klm  
Max.At90:19.88cd/klm  
Max.80-90:83.48cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	268
90%	241
80%	215
70%	188
60%	161
50%	134
40%	107
30%	80
20%	54
10%	27
5%	13

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks:

COEFFICIENT OF UTILIZATION CURVE  
AND ISOLUX DIAGRAM

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature: 25.3 °C  
Operators: DAMIN  
Test Date: 2024-03-08

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 0.5DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity: 65.0%  
Test Distance: 9.780m [K=1.0000]  
Remarks:

### ZONAL FLUX DIAGRAM

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	2.255	2.750	2.928	2.801	2.281	2.347	2.424	2.212	0- 10	0.2280	0.2280	0.04,0.04
20	92.22	26.67	42.90	14.53	38.22	8.546	56.84	16.46	10- 20	3.858	4.086	0.69,0.69
30	157.0	145.3	151.1	139.9	154.8	134.7	157.7	163.7	20- 30	45.28	49.36	8.3,8.3
40	142.0	257.2	145.6	257.2	148.0	257.0	145.0	253.1	30- 40	108.4	157.8	26.5,26.5
50	115.7	221.3	122.8	226.4	125.7	226.7	122.0	216.4	40- 50	134.6	292.4	49.1,49.1
60	82.79	163.4	92.10	170.3	95.15	173.0	91.74	152.0	50- 60	126.3	418.7	70.4,70.4
70	47.85	96.42	55.90	104.7	60.62	110.6	56.95	90.37	60- 70	96.60	515.3	86.6,86.6
80	16.59	32.97	21.85	40.79	26.87	47.34	22.45	28.70	70- 80	53.24	568.6	95.5,95.5
90	9.738	7.488	9.261	8.245	11.36	11.12	10.35	9.414	80- 90	17.26	585.9	98.4,98.4
100	1.928	1.408	2.539	1.480	3.637	2.144	2.745	1.435	90-100	5.300	591.2	99.3,99.3
110	1.843	0.6162	1.111	0.5521	3.182	0.6906	0.9220	0.6028	100-110	1.671	592.8	99.6,99.6
120	0.5015	0.4505	0.9681	0.4167	0.6358	0.6435	0.6908	0.5892	110-120	0.8152	593.6	99.8,99.8
130	0.3590	0.5655	0.4401	0.6266	0.4338	0.6976	0.7112	0.5789	120-130	0.5149	594.2	99.8,99.8
140	0.4741	0.6195	0.5633	0.5585	0.6363	0.6095	0.4809	0.4437	130-140	0.4383	594.6	99.9,99.9
150	0.3931	0.4809	0.4060	0.4775	0.4465	0.3453	0.2646	0.3014	140-150	0.3063	594.9	100,100
160	0.3319	0.2744	0.3591	0.2743	0.1896	0.1592	0.1287	0.1591	150-160	0.1387	595.0	100,100
170	0.1494	0.1424	0.1083	0.1591	0.0608	0.0744	0.0746	0.0542	160-170	0.0473	595.1	100,100
180	0.0068	0.0237	0.0135	0.0305	0	0.0135	0.0068	0.0271	170-180	0.0059	595.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks:

ISOCANDELA DIAGRAM


Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks:

### Planar Illuminance Curve




C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3 °C  
 Operators: DAMIN  
 Test Date: 2024-03-08

γ Range: 0 - 180DEG  
 γ Interval: 0.5DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
 Humidity: 65.0%  
 Test Distance: 9.780m [K=1.0000]  
 Remarks:

**LCS REPORT**

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

**LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH**


C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3℃  
 Operators:DAMIN  
 Test Date:2024-03-08

γ Range: 0 - 180DEG  
 γ Interval: 0.5DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
 Humidity:65.0%  
 Test Distance:9.780m [K=1.0000]  
 Remarks:

### BUG REPORT

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

#### IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	28.29	4.8
FM - Front-Medium(30-60)	190.62	32.0
FH - Front-High(60-80)	74.033	12.4
FVH - Front-Very High(80-90)	8.1696	1.4
Total Forward Light	305.7	51.4

BL - Back-Low(0-30)	21.073	3.5
BM - Back-Medium(30-60)	178.76	30.0
BH - Back-High(60-80)	75.807	12.7
BVH - Back-Very High(80-90)	9.093	1.5
Total Back Light	289.39	48.6

UL - Uplight-Low(90-100)	5.3003	0.9
UH - Uplight-High(100-180)	3.9375	0.7
Total Up Light	9.2378	1.6

BUG(Back,Up,Glare) Rating	B0-U1-G0
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	284.74	4.6484	289.39
Street Side	301.11	4.5894	305.7


C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks:

ROAD ISOCANDELA REPORT

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks:

### LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm		
NAME: LED BOLLARD	TYPE: LED	WEIGHT: 5
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	2.38	2.32	2.33	2.30	2.26	2.23	2.23	2.23	2.24	2.27	2.21	2.24	2.18	2.26	2.18	2.24	2.18	2.25	2.38
5	2.27	2.30	2.32	2.31	2.28	2.34	2.27	2.33	2.27	2.36	2.33	2.41	2.41	2.53	2.51	2.62	2.57	2.63	2.49
10	2.26	2.40	2.53	2.72	2.72	2.78	2.77	2.89	2.87	2.93	2.82	2.85	2.75	2.82	2.78	2.86	2.72	2.60	2.28
15	26.3	22.5	16.9	9.98	4.67	4.25	7.62	11.1	14.1	14.2	12.8	9.03	5.08	3.51	3.20	3.05	6.09	8.04	2.02
20	92.2	85.1	71.7	50.0	30.5	22.8	28.4	36.4	42.1	42.9	39.8	31.8	22.4	12.8	16.2	31.0	47.6	56.4	38.2
25	151	145	133	111	87.7	61.6	61.7	80.5	96.9	102	101	86.6	62.8	53.5	69.3	89.7	112	122	107
30	157	157	157	156	148	142	133	139	150	151	149	142	139	142	138	146	151	154	155
35	151	151	152	166	218	233	192	154	152	152	152	153	193	235	212	162	150	150	155
40	142	142	143	197	255	259	213	151	145	146	145	151	210	262	253	180	144	142	148
45	130	130	139	214	243	244	209	143	135	135	136	143	206	247	248	193	136	132	138
50	116	116	132	203	221	221	189	130	122	123	123	131	188	226	227	188	124	119	126
55	99.7	101	118	179	194	194	164	114	108	108	109	116	166	200	200	173	111	105	111
60	82.8	83.6	102	151	164	163	135	95.8	91.3	92.1	92.5	99.2	141	170	171	149	97.3	88.7	95.2
65	65.4	66.1	84.3	121	131	130	104	76.8	73.6	74.3	75.1	80.9	113	138	139	120	79.3	71.6	78.4
70	47.8	48.5	63.0	88.5	97.2	95.6	75.3	57.2	55.3	55.9	56.8	61.2	83.7	104	105	90.7	60.0	54.3	60.6
75	30.9	31.5	40.6	57.1	63.7	62.4	48.4	38.5	37.2	37.8	38.6	42.1	56.6	71.3	72.2	61.9	41.0	37.2	43.2
80	16.6	17.1	20.8	28.7	33.4	32.5	25.7	21.9	21.5	21.8	22.5	24.5	32.2	40.4	41.2	35.0	24.0	22.3	26.9
85	11.5	11.4	11.2	12.1	14.8	13.6	12.6	13.0	13.3	13.1	13.0	13.0	13.6	15.5	15.2	13.8	12.9	12.7	14.6
90	9.74	9.56	8.35	8.32	7.39	7.58	8.33	9.00	9.44	9.26	8.89	8.48	7.82	8.30	8.19	8.03	9.71	10.6	11.4
95	5.22	4.79	3.04	2.83	2.00	2.63	3.28	3.73	4.20	3.96	3.86	3.46	3.04	2.52	2.69	3.11	4.80	6.21	8.10
100	1.93	1.73	1.30	1.12	1.10	1.72	2.28	2.64	2.97	2.54	2.73	2.32	1.92	1.63	1.33	1.39	2.68	3.48	3.64
105	1.90	1.85	1.00	0.68	0.75	0.77	1.13	1.44	1.83	1.62	1.59	1.12	0.87	0.64	0.89	1.15	2.70	3.43	3.74
110	1.84	1.71	1.08	0.57	0.57	0.66	0.88	0.93	1.21	1.11	0.98	0.75	0.69	0.51	0.60	0.84	2.12	2.76	3.18
115	0.98	0.88	0.64	0.45	0.49	0.56	0.83	0.83	1.11	1.08	0.90	0.72	0.65	0.44	0.41	0.42	0.80	0.99	1.46
120	0.50	0.45	0.50	0.47	0.43	0.47	0.70	0.72	0.94	0.97	0.81	0.64	0.54	0.45	0.38	0.40	0.50	0.49	0.64
125	0.37	0.45	0.50	0.47	0.45	0.54	0.52	0.49	0.65	0.70	0.64	0.49	0.51	0.59	0.49	0.43	0.43	0.35	0.43
130	0.36	0.41	0.44	0.53	0.53	0.60	0.52	0.52	0.43	0.44	0.47	0.54	0.54	0.62	0.63	0.60	0.53	0.43	0.43
135	0.43	0.50	0.50	0.53	0.55	0.71	0.54	0.54	0.43	0.46	0.47	0.55	0.56	0.62	0.63	0.60	0.77	0.57	0.66
140	0.47	0.49	0.54	0.54	0.58	0.66	0.68	0.56	0.49	0.56	0.72	0.70	0.61	0.51	0.60	0.60	0.75	0.57	0.64
145	0.47	0.43	0.54	0.55	0.51	0.51	0.55	0.43	0.54	0.55	0.73	0.60	0.44	0.43	0.57	0.56	0.58	0.52	0.55
150	0.39	0.33	0.45	0.46	0.54	0.43	0.35	0.30	0.40	0.41	0.56	0.32	0.34	0.40	0.56	0.47	0.48	0.42	0.45
155	0.33	0.29	0.38	0.30	0.32	0.42	0.34	0.30	0.30	0.29	0.30	0.45	0.51	0.38	0.35	0.30	0.40	0.35	0.32
160	0.33	0.19	0.27	0.24	0.31	0.24	0.26	0.22	0.31	0.36	0.47	0.38	0.30	0.24	0.30	0.21	0.25	0.35	0.19
165	0.29	0.17	0.22	0.17	0.28	0.21	0.24	0.16	0.20	0.16	0.23	0.20	0.28	0.20	0.26	0.16	0.24	0.28	0.19
170	0.15	0.05	0.14	0.09	0.18	0.11	0.18	0.11	0.18	0.11	0.18	0.12	0.20	0.13	0.19	0.11	0.18	0.12	0.06
175	0.07	0.02	0.08	0.02	0.10	0.03	0.09	0.03	0.09	0.01	0.07	0.02	0.07	0.04	0.10	0.03	0.11	0.04	0.00
180	0.01	0.00	0.00	0.00	0.03	0.02	0.02	0.01	0.02	0.01	0.02	0.02	0.03	0.03	0.03	0.02	0.02	0.01	0.00

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.78V I:0.0974A P:20.901W PF:0.9715 Freq:49.99Hz Lamp Flux:595.088x1 lm																	
NAME: LED BOLLARD									TYPE: LED						WEIGHT: 5		
SPEC.:									DIM.:						SERIAL No.: 1		
MFR.: EVERFINE									SUR.:						Shielding Angle:		

Table--2

UNIT: cd

C (DEG) γ (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	2.32	2.33	2.30	2.26	2.23	2.23	2.23	2.24	2.27	2.21	2.24	2.18	2.26	2.18	2.24	2.18	2.25		
5	2.46	2.41	2.35	2.34	2.27	2.36	2.29	2.31	2.24	2.24	2.15	2.12	2.09	2.07	2.07	2.07	2.06		
10	2.36	2.32	2.38	2.32	2.37	2.60	2.53	2.54	2.42	2.40	2.28	2.32	2.21	2.21	2.12	2.23	2.22		
15	2.01	2.15	2.24	2.75	3.42	4.00	5.69	6.82	7.40	5.99	3.94	2.34	2.30	2.32	5.48	9.11	12.5		
20	34.8	24.3	13.8	6.32	10.8	20.3	38.2	52.2	56.8	51.0	40.0	22.9	13.7	19.2	38.4	54.5	66.1		
25	101	85.0	63.0	42.1	43.6	77.4	109	122	125	118	103	82.9	74.7	74.9	97.2	118	131		
30	152	142	129	130	139	143	155	158	158	155	149	155	169	159	145	153	156		
35	154	154	190	232	217	167	154	154	153	152	156	202	246	226	158	149	150		
40	147	158	224	268	246	176	147	146	145	144	155	213	259	247	175	142	142		
45	137	163	237	255	240	176	139	136	134	134	141	194	240	240	184	134	131		
50	125	157	223	234	220	165	128	123	122	122	127	164	214	219	175	123	118		
55	111	141	199	208	195	145	113	109	108	108	113	133	178	192	158	108	103		
60	94.9	121	171	179	167	125	97.3	92.9	91.7	92.1	98.6	123	142	162	138	91.3	86.8		
65	77.9	101	140	147	138	103	79.7	76.3	74.9	75.2	81.3	107	111	130	114	75.5	69.5		
70	60.5	78.8	109	115	107	79.3	61.6	58.9	56.9	56.7	60.3	81.6	83.5	97.3	84.3	56.5	52.2		
75	43.2	56.7	76.8	81.6	75.3	55.6	43.3	40.8	38.9	38.2	39.8	57.1	55.7	64.7	57.3	37.9	35.3		
80	26.9	34.8	46.3	49.7	45.0	33.5	26.3	24.2	22.5	21.5	23.2	31.0	27.8	29.6	26.0	22.1	20.2		
85	14.5	16.9	20.7	22.4	19.1	15.6	14.0	13.5	13.0	12.9	12.8	14.0	14.4	13.1	11.6	11.5	11.7		
90	11.0	10.1	10.2	11.8	10.4	9.99	10.4	10.6	10.3	10.1	9.44	9.10	9.80	9.03	9.15	9.71	10.1		
95	7.36	4.81	4.26	4.13	3.49	4.23	4.78	5.19	5.05	4.92	4.31	3.78	3.16	3.40	3.71	5.07	6.58		
100	3.33	2.11	1.74	2.14	2.15	2.58	2.98	3.16	2.75	2.98	2.69	2.27	1.73	1.14	1.41	1.80	2.42		
105	3.39	1.81	1.06	1.22	1.06	1.46	1.95	2.02	1.82	1.97	1.70	1.21	0.87	0.60	0.82	1.27	1.64		
110	2.91	1.92	0.96	0.70	0.68	0.72	0.97	0.93	0.92	0.85	0.83	0.70	0.65	0.56	0.75	1.27	1.82		
115	1.29	0.76	0.65	0.60	0.68	0.77	0.83	0.81	0.69	0.68	0.72	0.70	0.62	0.56	0.66	0.95	1.36		
120	0.66	0.50	0.56	0.60	0.68	0.81	0.85	0.81	0.69	0.68	0.72	0.70	0.62	0.56	0.56	0.51	0.68		
125	0.47	0.48	0.53	0.68	0.72	0.81	0.85	0.81	0.70	0.68	0.75	0.69	0.62	0.54	0.56	0.51	0.49		
130	0.45	0.58	0.62	0.67	0.72	0.72	0.80	0.72	0.71	0.62	0.70	0.63	0.62	0.53	0.52	0.50	0.47		
135	0.60	0.65	0.65	0.62	0.68	0.60	0.68	0.57	0.59	0.53	0.60	0.54	0.56	0.47	0.52	0.52	0.46		
140	0.66	0.63	0.66	0.59	0.63	0.48	0.52	0.46	0.48	0.41	0.47	0.41	0.48	0.41	0.51	0.52	0.47		
145	0.62	0.54	0.58	0.48	0.48	0.35	0.47	0.47	0.44	0.39	0.40	0.32	0.39	0.37	0.45	0.41	0.45		
150	0.51	0.42	0.49	0.37	0.33	0.20	0.26	0.18	0.26	0.22	0.35	0.23	0.32	0.28	0.38	0.33	0.36		
155	0.39	0.32	0.32	0.22	0.24	0.15	0.19	0.14	0.22	0.17	0.20	0.21	0.24	0.18	0.28	0.24	0.27		
160	0.18	0.10	0.18	0.13	0.19	0.12	0.17	0.09	0.13	0.10	0.16	0.24	0.18	0.14	0.18	0.11	0.20		
165	0.12	0.04	0.12	0.09	0.16	0.09	0.14	0.06	0.11	0.03	0.09	0.07	0.16	0.11	0.14	0.06	0.24		
170	0.11	0.03	0.09	0.04	0.11	0.03	0.08	0.01	0.07	0.01	0.07	0.02	0.08	0.03	0.07	0.01	0.11		
175	0.05	0.00	0.04	0.01	0.05	0.01	0.03	0.01	0.03	0.01	0.03	0.02	0.05	0.03	0.04	0.01	0.02		
180	0.00	0.00	0.02	0.01	0.02	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.03	0.03	0.03	0.01	0.01		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:DAMIN  
Test Date:2024-03-08

γ Range: 0 - 180DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.464  
Humidity:65.0%  
Test Distance:9.780m [K=1.0000]  
Remarks: