



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 52.89 lm/W
MODEL	DLW-LED-067A-10W	I _{max} (cd)	396.2	η street_up (%)	1.1	
NOMINAL POWER (W)	10	LOR (%)	100.0	η street_down (%)	48.4	
RATED VOLTAGE (V)	220	TOTAL FLUX (lm)	580.8	η house_up (%)	1.2	
NOMINAL FLUX (lm)	580.754	MAXIMUM @ (C, γ)	40,13.5	η house_down (%)	49.3	
LAMPS INSIDE	1	η up (%)	2.3	76 FLASHAREA (m2)	0.00100	
TEST VOLTAGE (V)	220	η down (%)	97.7	SLI	9.012	


INTENSITY DISTRIBUTION DIAGRAM
IN C PLANSMAX INTENSITY CONE SURFACE
DISTRIBUTION DIAGRAM

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3 °C
Operators: DAMIN
Test Date: 2023-11-06

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity: 65.0%
Test Distance: 9.780m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:





Classification:

IES:Type V - Very Short
CIE:Narrow - Short
IES:Cut-off
CIE:Semi-cut-off
Max.At80:21.14cd/klm
Max.At90:16.76cd/klm
Max.80-90:21.14cd/klm

ISOCANDELA DIAGRAM		
UNIT		cd
Imax=100%		396
90%		357
80%		317
70%		277
60%		238
50%		198
40%		158
30%		119
20%		79
10%		40
5%		20

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2023-11-06

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity:65.0%
Test Distance:9.780m [K=1.0000]
Remarks:

COEFFICIENT OF UTILIZATION CURVE
AND ISOLUX DIAGRAM

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3 °C
Operators: DAMIN
Test Date: 2023-11-06

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity: 65.0%
Test Distance: 9.780m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	0.2232	375.6	389.7	107.6	0.1761	4.215	225.5	2.688	0- 10	5.192	5.192	0.89,0.89
20	0.6968	381.5	364.8	187.3	0.1487	166.9	374.0	342.2	10- 20	57.77	62.96	10.8,10.8
30	1.117	349.0	332.2	178.0	0.0542	186.9	345.2	270.2	20- 30	94.09	157.1	27,27
40	1.050	307.1	290.0	154.8	0.0542	178.7	307.2	220.7	30- 40	113.7	270.8	46.6,46.6
50	0.7929	253.1	234.1	126.5	0.0542	163.6	256.2	178.6	40- 50	120.0	390.8	67.3,67.3
60	0.6097	181.5	150.5	69.71	0.1287	127.9	189.5	133.6	50- 60	108.7	499.5	86,86
70	0.4944	17.73	8.206	12.49	0.1422	15.07	19.33	39.46	60- 70	52.04	551.5	95,95
80	0.3863	11.29	2.997	10.15	0.1422	10.56	3.798	12.20	70- 80	9.367	560.9	96.6,96.6
90	0.2780	8.805	0.5826	8.382	0.1421	8.236	0.4741	9.245	80- 90	6.248	567.2	97.7,97.7
100	0.1087	4.853	0.9689	4.197	0.0679	5.062	0.9478	5.509	90-100	4.517	571.7	98.4,98.4
110	0.0340	2.723	1.491	2.506	0.0610	3.376	1.523	3.356	100-110	2.617	574.3	98.9,98.9
120	0.0135	2.360	2.134	2.201	0.0745	2.493	2.120	2.449	110-120	1.866	576.2	99.2,99.2
130	0.0135	1.907	2.771	1.846	0.0814	2.201	2.648	2.225	120-130	1.651	577.8	99.5,99.5
140	0.0401	1.189	2.477	1.094	0.1626	1.260	3.223	1.301	130-140	1.352	579.2	99.7,99.7
150	0.0339	1.655	1.714	1.598	0.2846	0.9889	1.763	1.538	140-150	0.8350	580.0	99.9,99.9
160	0.2502	0.5452	1.291	0.5181	0.5149	0.5693	1.586	0.5555	150-160	0.5202	580.5	100,100
170	0.4130	0.5655	0.9195	0.6064	0.5418	0.5791	0.5079	0.5215	160-170	0.1773	580.7	100,100
180	0.5418	0.6333	0.7247	0.6265	0.5418	0.6400	0.7044	0.5994	170-180	0.0570	580.8	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2023-11-06

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity:65.0%
Test Distance:9.780m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3 °C
 Operators: DAMIN
 Test Date: 2023-11-06

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.464
 Humidity: 65.0%
 Test Distance: 9.780m [K=1.0000]
 Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3 °C
 Operators: DAMIN
 Test Date: 2023-11-06

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.464
 Humidity: 65.0%
 Test Distance: 9.780m [K=1.0000]
 Remarks:

LCS REPORT

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3℃
Operators: DAMIN
Test Date: 2023-11-06

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity: 65.0%
Test Distance: 9.780m [K=1.0000]
Remarks:

BUG REPORT

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	84.854	14.6
FM - Front-Medium(30-60)	169.38	29.2
FH - Front-High(60-80)	23.621	4.1
FVH - Front-Very High(80-90)	3.0475	0.5
Total Forward Light	287.39	49.5

BL - Back-Low(0-30)	72.2	12.4
BM - Back-Medium(30-60)	173.07	29.8
BH - Back-High(60-80)	37.791	6.5
BVH - Back-Very High(80-90)	3.2002	0.6
Total Back Light	293.36	50.5

UL - Uplight-Low(90-100)	4.5166	0.8
UH - Uplight-High(100-180)	9.076	1.6
Total Up Light	13.593	2.3

BUG(Back,Up,Glare) Rating	B0-U1-G0
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	286.26	7.1022	293.36
Street Side	280.9	6.4904	287.39


C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2023-11-06

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity:65.0%
Test Distance:9.780m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators: DAMIN
Test Date: 2023-11-06

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity: 65.0%
Test Distance: 9.780m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	0.17	0.18	0.13	0.22	0.14	0.22	0.15	0.22	0.15	0.22	0.15	0.21	0.13	0.20	0.13	0.18	0.12	0.15	0.17
5	0.14	0.29	0.52	0.95	1.77	2.67	4.33	7.01	10.5	11.4	10.3	7.68	5.85	3.46	2.01	1.06	0.48	0.28	0.18
10	0.22	1.13	4.33	18.6	361	390	387	382	385	390	393	395	393	200	15.6	6.59	2.34	0.68	0.18
15	0.41	3.26	14.2	347	395	390	383	377	375	378	381	385	386	309	27.9	17.6	6.80	1.48	0.18
20	0.70	6.77	21.9	179	384	379	373	367	362	365	367	369	371	346	29.0	23.7	12.4	2.57	0.15
25	0.98	10.5	24.5	80.5	368	365	359	354	349	349	351	352	354	346	27.1	23.1	14.5	3.37	0.09
30	1.12	11.6	23.0	36.4	350	348	342	338	333	332	333	334	335	331	25.1	20.7	14.1	3.56	0.05
35	1.12	10.7	20.2	25.1	330	328	323	319	314	312	312	313	313	310	23.5	18.4	12.7	3.43	0.05
40	1.05	9.22	17.6	21.6	307	307	302	297	292	290	289	290	289	287	23.1	16.5	11.3	3.18	0.05
45	0.92	7.89	15.4	19.1	282	282	277	272	267	264	263	263	262	260	23.1	14.9	10.1	2.88	0.05
50	0.79	6.75	13.6	17.1	252	254	249	243	237	234	233	233	232	230	23.1	13.5	9.00	2.64	0.05
55	0.69	5.87	12.2	15.6	217	223	217	211	204	200	198	198	197	195	22.4	12.3	8.08	2.43	0.09
60	0.61	5.17	11.0	14.2	177	186	179	171	160	150	142	135	127	120	19.3	11.2	7.24	2.25	0.13
65	0.55	4.60	9.93	13.0	97.8	96.6	79.9	65.0	49.9	38.8	30.7	25.9	22.3	21.1	13.3	10.2	6.53	2.13	0.14
70	0.49	4.15	9.05	12.0	18.0	17.5	15.0	12.2	9.41	8.21	9.29	10.9	12.2	13.2	11.8	9.39	5.93	2.00	0.14
75	0.43	3.79	8.29	11.2	13.6	12.5	10.6	8.09	5.76	4.68	6.33	8.19	9.86	11.1	11.0	8.78	5.47	1.90	0.14
80	0.39	3.48	7.61	10.5	12.1	10.5	8.63	6.25	4.05	3.00	4.81	6.77	8.60	9.98	10.3	8.14	5.09	1.82	0.14
85	0.33	3.12	6.84	9.45	10.4	8.43	6.13	3.81	1.66	0.52	2.41	4.42	6.48	8.23	9.21	7.43	4.70	1.70	0.14
90	0.28	2.84	6.21	8.86	9.70	7.91	5.87	3.77	1.64	0.58	2.36	4.36	6.33	7.98	8.78	7.01	4.36	1.58	0.14
95	0.21	2.41	4.82	5.81	7.05	6.69	5.25	3.39	1.75	0.73	2.12	3.74	5.28	6.25	5.89	5.55	3.53	1.19	0.11
100	0.11	1.50	2.98	3.48	4.26	5.45	4.67	3.06	1.90	0.97	1.92	3.41	4.42	4.62	3.77	3.86	2.45	0.79	0.07
105	0.07	0.92	2.07	2.24	2.89	3.88	3.59	2.73	1.92	1.21	1.91	2.76	3.44	3.19	2.58	2.67	1.80	0.53	0.06
110	0.03	0.62	1.34	1.48	2.30	3.14	2.78	2.36	1.96	1.49	1.95	2.42	2.73	3.07	1.94	1.77	1.27	0.36	0.06
115	0.01	0.44	1.01	1.31	2.04	2.83	2.43	2.76	2.05	1.80	2.28	2.38	2.50	2.67	1.79	1.56	0.91	0.26	0.06
120	0.01	0.35	0.98	1.69	2.13	2.59	2.31	2.76	2.23	2.13	2.49	2.46	2.40	2.61	1.79	1.58	0.77	0.21	0.07
125	0.01	0.33	0.98	1.75	2.07	2.44	2.30	2.93	2.49	2.45	2.71	2.61	2.38	2.48	1.82	1.56	0.71	0.18	0.07
130	0.01	0.33	0.98	1.69	1.60	2.21	2.36	3.15	2.72	2.77	2.95	2.84	2.38	2.13	1.56	1.51	0.69	0.18	0.08
135	0.01	0.33	0.98	1.42	1.04	1.72	2.53	3.27	2.95	3.07	3.14	2.99	2.26	1.40	1.06	1.43	0.69	0.18	0.14
140	0.04	0.32	0.92	1.06	0.93	1.45	2.15	2.49	2.49	2.48	2.47	2.19	1.98	1.31	0.88	0.94	0.66	0.14	0.16
145	0.03	0.19	0.57	1.06	1.10	1.88	1.75	1.77	1.82	1.86	1.75	1.52	1.69	2.08	1.19	1.09	0.38	0.10	0.17
150	0.03	0.24	0.66	1.19	1.27	2.04	2.18	1.80	1.66	1.71	1.65	1.74	2.03	1.75	1.44	1.20	0.51	0.22	0.28
155	0.13	0.28	0.79	1.00	0.79	1.35	1.52	1.75	2.12	2.31	2.17	1.69	1.38	0.95	0.67	0.90	0.54	0.33	0.41
160	0.25	0.38	0.67	0.64	0.54	0.56	0.63	0.97	1.22	1.29	1.16	0.80	0.56	0.52	0.51	0.62	0.58	0.45	0.51
165	0.35	0.43	0.52	0.54	0.54	0.58	0.60	0.76	0.87	0.95	0.93	0.90	0.60	0.60	0.58	0.59	0.57	0.52	0.54
170	0.41	0.49	0.49	0.54	0.55	0.58	0.62	0.68	0.88	0.92	0.94	0.77	0.71	0.63	0.58	0.60	0.56	0.56	0.54
175	0.46	0.55	0.53	0.59	0.57	0.64	0.60	0.70	0.66	0.72	0.68	0.71	0.66	0.65	0.59	0.60	0.56	0.57	0.54
180	0.54	0.55	0.57	0.59	0.61	0.66	0.69	0.69	0.72	0.72	0.71	0.71	0.68	0.65	0.60	0.60	0.57	0.57	0.54

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2023-11-06

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity:65.0%
Test Distance:9.780m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LED BOLLARD	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--2

UNIT: cd

C (DEG) γ (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	0.18	0.13	0.22	0.14	0.22	0.15	0.22	0.15	0.22	0.15	0.21	0.13	0.20	0.13	0.18	0.12	0.15		
5	0.13	0.12	0.12	0.22	0.21	0.31	0.29	0.36	0.28	0.31	0.20	0.23	0.12	0.19	0.12	0.14	0.12		
10	0.11	0.38	1.17	2.75	5.68	9.90	28.5	176	226	161	65.6	7.62	3.89	1.49	0.63	0.29	0.12		
15	0.30	1.47	7.20	18.4	127	394	394	390	386	380	386	392	393	167	6.16	1.27	0.18		
20	0.79	5.67	20.3	28.2	306	383	381	378	374	373	379	386	391	293	18.1	4.50	0.50		
25	1.89	13.1	24.0	28.4	358	367	365	363	361	362	368	373	378	226	25.2	10.2	1.17		
30	3.19	14.9	22.5	27.7	346	349	348	347	345	348	353	358	362	179	25.4	14.8	2.03		
35	3.91	14.4	20.0	35.5	327	329	328	328	328	331	335	340	343	146	23.0	15.3	2.63		
40	4.10	13.2	17.8	52.6	305	307	307	307	307	311	316	320	323	119	20.4	14.1	2.86		
45	4.08	11.9	16.1	66.0	279	281	282	283	284	288	293	297	300	99.2	18.3	12.5	2.86		
50	3.87	10.7	14.6	76.3	251	253	254	255	256	261	266	271	274	83.2	16.4	11.1	2.74		
55	3.64	9.61	13.3	79.0	219	222	223	224	225	231	236	242	245	68.3	14.9	9.88	2.58		
60	3.41	8.67	12.2	75.5	180	185	186	188	190	196	202	208	212	55.3	13.6	8.82	2.42		
65	3.20	7.89	11.2	36.8	77.8	90.9	101	114	123	138	149	162	170	43.4	12.4	7.87	2.30		
70	3.02	7.20	10.4	14.1	16.0	15.5	14.6	15.9	19.3	29.0	38.1	49.9	57.3	21.6	11.3	7.08	2.18		
75	2.85	6.62	9.75	12.1	11.9	10.6	8.98	7.40	6.53	8.94	11.4	13.8	15.5	13.5	10.4	6.38	2.07		
80	2.50	6.02	9.23	11.0	10.1	8.65	6.73	4.82	3.80	5.78	8.04	10.3	12.3	12.1	9.65	5.81	1.98		
85	2.30	5.57	8.38	9.66	8.23	6.52	4.58	2.64	1.62	3.70	6.03	8.30	10.2	11.0	8.79	5.29	1.87		
90	2.16	4.91	7.95	9.03	7.44	5.48	3.49	1.51	0.47	2.47	4.63	6.77	8.76	9.73	7.92	4.75	1.74		
95	1.88	4.16	6.64	6.88	6.19	4.71	3.14	1.49	0.66	2.44	4.39	6.11	7.62	7.68	6.73	4.29	1.51		
100	1.42	2.97	4.37	4.72	5.40	4.39	2.66	1.63	0.95	2.27	4.17	5.58	6.43	4.59	4.06	2.66	1.06		
105	1.04	2.21	3.05	3.51	4.30	3.31	2.41	1.68	1.21	2.17	3.44	4.35	5.07	2.90	2.81	1.81	0.75		
110	0.80	1.62	2.12	2.98	3.77	3.11	2.54	1.92	1.52	2.43	3.42	3.92	4.67	2.04	1.77	1.20	0.53		
115	0.61	1.20	1.67	2.41	3.10	2.67	2.71	2.13	1.83	2.68	3.20	3.15	3.71	1.75	1.38	0.85	0.39		
120	0.52	1.17	1.56	2.31	2.68	2.52	2.78	2.30	2.12	2.79	2.99	2.72	3.06	1.84	1.56	0.81	0.32		
125	0.49	1.21	1.71	2.28	2.44	2.52	2.84	2.53	2.40	2.86	2.87	2.50	2.77	1.91	1.73	0.83	0.28		
130	0.46	1.20	1.75	1.97	2.43	2.54	2.80	2.65	2.65	3.03	2.90	2.49	2.60	1.85	1.73	0.83	0.28		
135	0.47	1.19	1.56	1.47	2.32	2.51	3.01	2.89	2.94	3.20	2.97	2.48	2.29	1.38	1.60	0.83	0.28		
140	0.51	0.95	1.11	0.79	1.73	2.16	3.02	3.24	3.22	3.20	2.80	2.08	1.64	0.96	1.29	0.72	0.30		
145	0.35	0.77	1.03	0.83	1.31	1.74	2.37	2.46	2.52	2.51	2.28	1.75	1.33	1.08	0.99	0.58	0.26		
150	0.49	1.14	1.50	0.64	1.34	1.51	1.51	1.64	1.76	1.70	1.54	1.85	1.84	1.23	1.12	0.72	0.24		
155	0.58	1.10	1.17	0.51	0.89	1.44	1.83	1.88	1.86	1.62	1.71	1.68	1.52	1.19	1.27	0.81	0.32		
160	0.56	0.60	0.58	0.51	0.63	1.09	1.36	1.48	1.59	1.33	1.06	1.03	0.56	0.55	0.72	0.59	0.37		
165	0.56	0.57	0.55	0.54	0.49	0.51	0.51	0.51	0.55	0.51	0.52	0.47	0.50	0.50	0.51	0.49	0.43		
170	0.56	0.57	0.55	0.61	0.55	0.68	0.72	0.68	0.51	0.54	0.48	0.50	0.49	0.56	0.49	0.52	0.47		
175	0.56	0.56	0.59	0.63	0.62	0.68	0.68	0.68	0.59	0.63	0.55	0.59	0.56	0.59	0.51	0.58	0.52		
180	0.56	0.56	0.59	0.62	0.66	0.68	0.68	0.70	0.70	0.70	0.68	0.68	0.60	0.60	0.57	0.58	0.57		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2023-11-06

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.464
Humidity:65.0%
Test Distance:9.780m [K=1.0000]
Remarks: